

# Safety Data Sheet



## 1. Identification

**Product Information:** M451-0410

**Product Name:** BLEND-IT HERON .5 OZ

**Recommended Use:** Surface Preparation or Protection

**Supplied by:** Mohawk Finishing Products  
Division of RPM Industrial Coatings Group  
3194 B Hickory Blvd  
Hudson, NC 28638  
USA

**Company Phone No:** (800) 522-8266

**Emergency Phone No. CHEMTREC:** (800) 424-9300

**International Emergency No. CHEMTREC:** (703) 527-3887 (Collect calls are accepted)

## 2. Hazards Identification

### GHS Classification

Asp. Tox. 1, Carc. 1B, Eye Dam. 1, Flam. Liq. 2, Muta. 1B, STOT RE 2, STOT SE 3 NE

### Symbol(s) of Product



### Signal Word

Danger

### Possible Hazards

1% of the mixture consists of ingredients of unknown acute toxicity

### GHS HAZARD STATEMENTS

|                                       |      |                                                                    |
|---------------------------------------|------|--------------------------------------------------------------------|
| Flammable Liquid, category 2          | H225 | Highly flammable liquid and vapour.                                |
| STOT, single exposure, category 3, NE | H336 | May cause drowsiness or dizziness.                                 |
| Germ Cell Mutagenicity, category 1B   | H340 | May cause genetic defects.                                         |
| Carcinogenicity, category 1B          | H350 | May cause cancer.                                                  |
| STOT, repeated exposure, category 2   | H373 | May cause damage to organs through prolonged or repeated exposure. |
| Aspiration Hazard, category 1         | H304 | May be fatal if swallowed and enters airways.                      |
| Serious Eye Damage, category 1        | H318 | Causes serious eye damage.                                         |

### GHS LABEL PRECAUTIONARY STATEMENTS

P403+P235 Store in a well-ventilated place. Keep cool.

### GHS SDS PRECAUTIONARY STATEMENTS

P210 Keep away from heat. - No smoking.

P240 Ground/Bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

|                |                                                                                                                                  |
|----------------|----------------------------------------------------------------------------------------------------------------------------------|
| P242           | Use only non-sparking tools.                                                                                                     |
| P243           | Take precautionary measures against static discharge.                                                                            |
| P280           | Wear eye protection/ face protection.                                                                                            |
| P331           | Do NOT induce vomiting.                                                                                                          |
| P405           | Store locked up.                                                                                                                 |
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.                       |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P403+P233      | Store in a well-ventilated place. Keep container tightly closed.                                                                 |
| P201           | Obtain special instructions before use.                                                                                          |
| P260           | Do not breathe dust/fume/gas/mist/vapors/spray.                                                                                  |
| P304+P340      | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.                                 |
| P308+P313      | IF exposed or concerned: Get medical advice/attention.                                                                           |
| P301+P310      | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.                                                              |

### 3. Composition/Information on ingredients

| <u>Chemical Name</u>                         | <u>CAS-No.</u> | <u>Wt. %</u> | <u>GHS Symbols</u> | <u>GHS Statements</u>        |
|----------------------------------------------|----------------|--------------|--------------------|------------------------------|
| titanium dioxide                             | 13463-67-7     | 10-30        | GHS08              | H351                         |
| n-butyl acetate                              | 123-86-4       | 10-30        | GHS02-GHS07        | H226-336                     |
| petroleum distillate                         | 64742-49-0     | 10-30        | GHS08              | H304-340-350                 |
| butanol                                      | 71-36-3        | 5-10         | GHS02-GHS05-GHS07  | H226-302-315-318-332-335-336 |
| pm acetate                                   | 108-65-6       | 5-10         | GHS02-GHS07        | H226-332                     |
| ethanol                                      | 64-17-5        | 1-5          | GHS02              | H225                         |
| aliphatic petroleum distillates              | 64742-47-8     | 1-5          | GHS07-GHS08        | H304-332                     |
| eep                                          | 763-69-9       | 1-5          | GHS06              | H331                         |
| toluene                                      | 108-88-3       | 1-5          | GHS02-GHS07-GHS08  | H225-304-315-332-336-373     |
| m-xylene                                     | 108-38-3       | 1-5          | GHS02-GHS07        | H226-315-332                 |
| ethylbenzene                                 | 100-41-4       | 0.1-1        | GHS02-GHS07-GHS08  | H225-304-332-373             |
| p-xylene                                     | 106-42-3       | 0.1-1        | GHS02-GHS07        | H226-315-332                 |
| carbon black                                 | 1333-86-4      | 0.1-1        | GHS02              | H251                         |
| polyoxyethylene dinonyphenyl ether phosphate | 39464-64-7     | <0.1         | No Information     | No Information               |
| cobalt octoate                               | 136-52-7       | <0.1         | No Information     | No Information               |
| surfactant                                   | 68891-21-4     | <0.1         | No Information     | No Information               |

The exact percentage (concentration) of ingredients is being withheld as a trade secret.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

### 4. First-aid Measures



FIRST AID - EYE CONTACT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

FIRST AID - SKIN CONTACT: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

FIRST AID - INGESTION: Do NOT induce vomiting. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

FIRST AID - INHALATION: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

## 5. Fire-fighting Measures

**SPECIAL FIREFIGHTING PROCEDURES:** Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

**FIREFIGHTING EQUIPMENT:** This is a NFPA/OSHA Class 1B or less flammable liquid. Follow NFPA30, Chapter 16 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipient fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire.

## 6. Accidental Release Measures

**ENVIRONMENTAL MEASURES:** No Information

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

## 7. Handling and Storage



**HANDLING:** Avoid inhalation and contact with eyes, skin, and clothing. Wash hands thoroughly after handling and before eating or drinking. In keeping with safe handling practices, avoid ignition sources (smoking, flames, pilot lights, electrical sparks); ground and bond containers when transferring the material to prevent static electricity sparks that could ignite vapor and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

**STORAGE:** Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

## 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

| <u>Chemical Name</u>                | <u>ACGIH TLV-TWA</u>  | <u>ACGIH-TLV STEL</u> | <u>OSHA PEL-TWA</u>   | <u>OSHA PEL-CEILING</u> |
|-------------------------------------|-----------------------|-----------------------|-----------------------|-------------------------|
| titanium dioxide                    | 0.2 mg/m <sup>3</sup> | N.D.                  | 15 mg/m <sup>3</sup>  | N.D.                    |
| n-butyl acetate                     | 50 ppm                | 150 ppm               | 150 ppm               | N.D.                    |
| petroleum distillate                | 100 ppm               | N.D.                  | N.D.                  | N.D.                    |
| butanol                             | 20 ppm                | N.D.                  | 100 ppm               | N.D.                    |
| pm acetate                          | N.D.                  | N.D.                  | N.D.                  | N.D.                    |
| ethanol                             | N.D.                  | 1000 ppm              | 1000 ppm              | N.D.                    |
| aliphatic petroleum distillates     | N.D.                  | N.D.                  | N.D.                  | N.D.                    |
| eeep                                | N.D.                  | N.D.                  | N.D.                  | N.D.                    |
| toluene                             | 20 ppm                | N.D.                  | 200 ppm               | 300 ppm                 |
| m-xylene                            | 20 ppm                | N.D.                  | 100 ppm               | N.D.                    |
| ethylbenzene                        | 20 ppm                | N.D.                  | 100 ppm               | N.D.                    |
| p-xylene                            | 20 ppm                | N.D.                  | 100 ppm               | N.D.                    |
| carbon black                        | 3 mg/m <sup>3</sup>   | N.D.                  | 3.5 mg/m <sup>3</sup> | N.D.                    |
| polyoxyethylene dinonylphenyl ether | N.D.                  | N.D.                  | N.D.                  | N.D.                    |
| phosphate                           |                       |                       |                       |                         |
| cobalt octoate                      | N.D.                  | N.D.                  | N.D.                  | N.D.                    |
| surfactant                          | N.D.                  | N.D.                  | N.D.                  | N.D.                    |

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established N.D. = Not Determined

## Personal Protection



**RESPIRATORY PROTECTION:** Use adequate engineering controls and ventilation to keep levels below recommended or statutory exposure limits. If exposure levels exceed limits use appropriate approved respiratory protection equipment.



**SKIN PROTECTION:** Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.



**EYE PROTECTION:** Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.



**OTHER PROTECTIVE EQUIPMENT:** No Information



**HYGIENIC PRACTICES:** It is good practice to avoid contact with the product and/or its vapors, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

## 9. Physical and Chemical Properties

|                                       |                           |                                                     |                |
|---------------------------------------|---------------------------|-----------------------------------------------------|----------------|
| <b>Appearance:</b>                    | Colored Liquid            | <b>Physical State:</b>                              | Liquid         |
| <b>Odor:</b>                          | Strong Solvent            | <b>Odor Threshold:</b>                              | Not Determined |
| <b>Density, g/cm3:</b>                | 1.157                     | <b>pH:</b>                                          | Not Determined |
| <b>Freeze Point, °F:</b>              | Not Determined            | <b>Viscosity:</b>                                   | Not Determined |
| <b>Solubility in Water:</b>           | Not Determined            | <b>Partition Coefficient, n-octanol/<br/>water:</b> | Not Determined |
| <b>Decomposition temperature, °F:</b> | Not Determined            | <b>Explosive Limits, %:</b>                         | Not Determined |
| <b>Boiling Range, °F:</b>             | > 100 °F                  | <b>Flash Point, °F:</b>                             | 55.4           |
| <b>Combustibility:</b>                | Supports Combustion       | <b>Auto-Ignition Temperature, °F:</b>               | Not Determined |
| <b>Evaporation Rate:</b>              | Faster than Diethyl Ether | <b>Vapor Pressure, mmHg:</b>                        | Not determined |
| <b>Vapor Density:</b>                 | Not Determined            | <b>Color:</b>                                       | Gray           |
| N.I. = No Information                 |                           |                                                     |                |

## 10. Stability and reactivity

**STABILITY:** Stable under normal conditions.

**CONDITIONS TO AVOID:** Heat, flames and sparks.

**INCOMPATIBILITY:** Acids, Bases, Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Not determined.

## 11. Toxicological information



### Practical Experiences

EMERGENCY OVERVIEW: No Information

EFFECT OF OVEREXPOSURE - EYE CONTACT: No Information

EFFECT OF OVEREXPOSURE - INGESTION: No Information

EFFECT OF OVEREXPOSURE - INHALATION: No Information

EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information

CARCINOGENICITY: May cause cancer.

This product contains Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

PRIMARY ROUTE(S) OF ENTRY:

Eye Contact, Skin Contact, Ingestion, Inhalation

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

| <u>CAS-No.</u> | <u>Chemical Name</u>            | <u>Oral LD50</u> | <u>Dermal LD50</u>  | <u>Vapor LC50</u> |
|----------------|---------------------------------|------------------|---------------------|-------------------|
| 13463-67-7     | titanium dioxide                | >10000 mg/kg Rat | >10000 mg/kg Rabbit | >20 mg/l          |
| 123-86-4       | n-butyl acetate                 | 14130 mg/kg Rat  | >17600 mg/kg Rabbit | 23.4 mg/l Rat     |
| 64742-49-0     | petroleum distillate            | >5000 mg/kg Rat  | >3160 mg/kg Rabbit  | 54 mg/l Rat       |
| 71-36-3        | butanol                         | 700 mg/kg Rat    | 3402 mg/kg Rabbit   | 8000 mg/l Rat     |
| 108-65-6       | pm acetate                      | 8532 mg/kg Rat   | >5000 mg/kg Rabbit  | >20 mg/L          |
| 64-17-5        | ethanol                         | 7060 mg/kg Rat   | 15,800 mg/kg        | 124.7 mg/L Rat    |
| 64742-47-8     | aliphatic petroleum distillates | >5000 mg/kg Rat  | >2000 mg/kg Rabbit  | >13 mg/L Rat      |
| 763-69-9       | eep                             | 3200 mg/kg Rat   | 4080 mg/kg Rabbit   | >20 mg/l          |
| 108-88-3       | toluene                         | 2600 mg/kg Rat   | 12000 mg/kg Rabbit  | 12.5 mg/L Rat     |
| 108-38-3       | m-xylene                        | 5000 mg/kg Rat   | 6500 mg/kg Rabbit   | >20 mg/l Rat      |
| 100-41-4       | ethylbenzene                    | 3500 mg/kg Rat   | 15400 mg/kg Rabbit  | 17.2 mg/L Rat     |
| 106-42-3       | p-xylene                        | 4029 mg/kg Rat   | >2000 mg/kg rabbit  | >20 mg/l Rat      |
| 1333-86-4      | carbon black                    | >5000 mg/kg Rat  | >3000 mg/kg Rabbit  | >20 mg/l          |
| 136-52-7       | cobalt octoate                  | 3129 mg/kg Rat   | >5000 mg/kg Rabbit  | N.I.              |

N.I. = No Information

## 12. Ecological information

**ECOLOGICAL INFORMATION:** Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

### 13. Disposal Information



Product

**DISPOSAL METHOD:** Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

### 14. Transport Information

**SPECIAL TRANSPORT PRECAUTIONS:** No Information

**DOT:** UN1263, PAINT, 3, II

**IATA:** UN1263, PAINT, 3, II

**IMDG:** UN1263, PAINT, 3, II

### 15. Regulatory Information

#### U.S. Federal Regulations:

##### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

##### SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>Chemical Name</u> | <u>CAS-No.</u> | <u>Wt. %</u> |
|----------------------|----------------|--------------|
| butanol              | 71-36-3        | 6.03         |
| toluene              | 108-88-3       | 1.62         |
| m-xylene             | 108-38-3       | 1.28         |

##### TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

| <u>Chemical Name</u>         | <u>CAS-No.</u> |
|------------------------------|----------------|
| octamethylcyclotetrasiloxane | 556-67-2       |

**U.S. State Regulations:****CALIFORNIA PROPOSITION 65**WARNING: Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Titanium Dioxide, Cancer, 27.068%

Toluene, Reproductive Harm, 1.6244%

**16. Other Information****Revision Date:** 7/27/2025 **Supersedes Date:** 7/28/2024

**Reason for revision:** Product Composition Changed  
Substance and/or Product Properties Changed in Section(s):  
02 - Hazards Identification  
05 - Flammability Information  
09 - Physical & Chemical Information  
14 - Transportation Information  
15 - Regulatory Information  
16 - Other Information

**Datasheet produced by:** Regulatory Department**HMIS Ratings:**

|                |   |                      |   |                    |   |                             |   |
|----------------|---|----------------------|---|--------------------|---|-----------------------------|---|
| <b>Health:</b> | 2 | <b>Flammability:</b> | 3 | <b>Reactivity:</b> | 0 | <b>Personal Protection:</b> | X |
|----------------|---|----------------------|---|--------------------|---|-----------------------------|---|

**Volatile Organic Compounds, gr/ltr:** 598

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

Only the original U.S. - English version is authoritative.