# Safety Data Sheet



## 1. Identification

Product Information: M500-2076

Product Name: BASE CONCENTRATE MEDIUM BROWN WALNUT QT

Recommended Use: Surface Preparation or Protection

Mohawk Finishing Products Supplied by:

Division of RPM Industrial Coatings Group

2220 US Hwy 70 SE Suite 100

Hickory, NC 28602

(800) 424-9300

USA

Company Phone No: (800) 522-8266 **Emergency Phone No. CHEMTREC:** 

International Emergency No. CHEMTREC: (703) 527-3887 (Collect calls are accepted)

## 2. Hazards Identification

#### **GHS Classification**

Carc. 1B, Flam. Liq. 2, Muta. 1B, Skin Irrit. 2, Skin Sens. 1, STOT RE 2

#### Symbol(s) of Product







Signal Word Danger

## **GHS HAZARD STATEMENTS**

H225 Highly flammable liquid and vapour. Flammable Liquid, category 2

Skin Irritation, category 2 H315 Causes skin irritation.

Skin Sensitizer, category 1 H317 May cause an allergic skin reaction.

Germ Cell Mutagenicity, category 1B H340 May cause genetic defects.

Carcinogenicity, category 1B H350 May cause cancer.

STOT, repeated exposure, category 2 H373 May cause damage to organs through prolonged or repeated exposure.

#### **GHS LABEL PRECAUTIONARY STATEMENTS**

Take off contaminated clothing and wash it before reuse. P362+P364

P403+P235 Store in a well-ventilated place. Keep cool.

#### **GHS SDS PRECAUTIONARY STATEMENTS**

P210 Keep away from heat. - No smoking.

P233 Keep container tightly closed.

P240 Ground/Bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash face, hands and any exposed skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear eye protection/ face protection.

P314 Get medical advice/attention if you feel unwell.

P405 Store locked up.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P201 Obtain special instructions before use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

## 3. Composition/Information on ingredients

Chemical Name	CAS-No.	<u>Wt. %</u>	GHS Symbols	GHS Statements
petroleum distillate	64742-49-0	2.5-10	GHS08	H304-340-350
m-xylene	108-38-3	2.5-10	GHS02-GHS07	H226-315-332
petroleum distillate	64742-48-9	2.5-10	GHS08	H304-340-350
o-xylene	95-47-6	2.5-10	GHS02-GHS07	H226-315-332
ethylbenzene	100-41-4	2.5-10	GHS02-GHS07-	H225-304-332-373
•			GHS08	
n-butyl acetate	123-86-4	2.5-10	GHS02-GHS07	H226-336
p-xylene	106-42-3	2.5-10	GHS02-GHS07	H226-315-332
aromatic hydrocarbons	64742-95-6	1.0-2.5	GHS06-GHS08	H304-331-340-350
propylene glycol monomethyl ether	107-98-2	1.0-2.5	GHS02-GHS06-	H226-331-336
			GHS07	
1,2,4-trimethylbenzene	95-63-6	1.0-2.5	GHS02-GHS07	H226-315-319-332-335
crystalline silica	14808-60-7	0.1-1.0	No Information	No Information
methyl ethyl ketoxime	96-29-7	0.1-1.0	GHS05-GHS06-	H302-311-315-317-318-331-336
			GHS07-GHS08	-350-370-373
carbon black	1333-86-4	0.1-1.0	GHS02	H251
cumene	98-82-8	0.1-1.0	GHS02-GHS07-	H226-302-304-332-335-350
			GHS08	

The exact percentage (concentration) of ingredients is being withheld as a trade secret.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

#### 4. First-aid Measures



FIRST AID - EYE CONTACT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

FIRST AID - SKIN CONTACT: IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention.

FIRST AID - INGESTION: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

FIRST AID - INHALATION: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

## 5. Fire-fighting Measures

SPECIAL FIREFIGHTING PROCEDURES: Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

**FIREFIGHTING EQUIPMENT:** This is a NFPA/OSHA Class 1B or less flammable liquid. Follow NFPA30, Chapter 16 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipeint fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire.

#### Accidental Release Measures

**ENVIRONMENTAL MEASURES:** No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

# 7. Handling and Storage





**HANDLING:** Avoid inhalation and contact with eyes, skin, and clothing. Wash hands thoroughly after handling and before eating or drinking. In keeping with safe handling practices, avoid ignition sources (smoking, flames, pilot lights, electrical sparks); ground and bond containers when transferring the material to prevent static electricity sparks that could ignite vapor and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

STORAGE: Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

## 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
petroleum distillate	100 ppm	N.D.	N.D.	N.D.
m-xylene	20 ppm	N.D.	100 ppm	N.D.
petroleum distillate	N.D.	N.D.	N.D.	N.D.
o-xylene	20 ppm	N.D.	N.D.	N.D.
ethylbenzene	20 ppm	N.D.	100 ppm	N.D.
n-butyl acetate	50 ppm	150 ppm	150 ppm	N.D.
p-xylene	20 ppm	N.D.	100 ppm	N.D.
aromatic hydrocarbons	N.D.	N.D.	N.D.	N.D.
propylene glycol monomethyl ether	50 ppm	100 ppm	N.D.	N.D.
1,2,4-trimethylbenzene	10 ppm	N.D.	N.D.	N.D.
crystalline silica	0.025 mg/m3	N.D.	50 μg/m3	N.D.
methyl ethyl ketoxime	N.D.	N.D.	N.D.	N.D.
carbon black	3 mg/m3	N.D.	3.5 mg/m3	N.D.
cumene	5 ppm	N.D.	50 ppm	N.D.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established N.D. = Not Determined

#### Personal Protection



**RESPIRATORY PROTECTION:** Use adequate engineering controls and ventilation to keep levels below recommended or statutory exposure limits. If exposure levels exceed limits use appropriate approved respiratory protection equipment.



**SKIN PROTECTION:** Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.



**EYE PROTECTION:** Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.



OTHER PROTECTIVE EQUIPMENT: No Information



**HYGIENIC PRACTICES:** It is good practice to avoid contact with the product and/or its vapors, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

# 9. Physical and Chemical Properties

Appearance: Colored Liquid Physical State: Liquid

Odor: Strong Solvent Odor Threshold: Not Determined

Density, g/cm3:

1.089

PH:

Not Determined

Viscosity:

Partition Coefficient, n-octanol/

Not Determined

Not Determined

Solubility in Water:

Not Determined

Boiling Range, °F: > 100 °F Flash Point, °F: 63 ° F

Combustibility:Supports CombustionAuto-Ignition Temperature, °F:Not DeterminedEvaporation Rate:Faster than Diethyl EtherVapor Pressure, mmHg:Not Determined

Vapor Density: Not Determined

N.I. = No Information

## 10. Stability and reactivity

STABILITY: Stable under normal conditions.

**CONDITIONS TO AVOID:** Heat, flames and sparks. **INCOMPATIBILITY:** Acids, Bases, Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Not determined.

## 11. Toxicological information



# **Practical Experiences**

**EMERGENCY OVERVIEW:** No Information

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** No Information

**EFFECT OF OVEREXPOSURE - INGESTION:** No Information

EFFECT OF OVEREXPOSURE - INHALATION: No Information

**EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information** 

**CARCINOGENICITY:** May cause cancer.

PRIMARY ROUTE(S) OF ENTRY:

**Skin Contact** 

#### **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below

Chemical Name petroleum distillate	Oral LD50 >5000 mg/kg Rat	Dermal LD50 >3160 mg/kg Rabbit	Vapor LC50 54 mg/l Rat
m-xylene	5000 mg/kg Rat	6500 mg/kg Rabbit	>20 mg/l Rat
petroleum distillate	>5000 mg/kg Rat	>3160 mg/kg Rabbit	>20 mg/L Rat
o-xylene	3608 mg/kg Rat	14100 mg/kg Rabbit	>20 mg/l Rat
ethylbenzene	3500 mg/kg Rat	15400 mg/kg Rabbit	17.2 mg/L Rat
n-butyl acetate	14130 mg/kg Rat	>17600 mg/kg Rabbit	23.4 mg/l Rat
p-xylene	4029 mg/kg Rat	>2000 mg/kg rabbit	>20 mg/l Rat
aromatic hydrocarbons	14000 mg/kg Rat	>2000 mg/kg Rabbit	>4.96 mg/l Rat
propylene glycol monomethyl ether	5000 mg/kg Rat	13000 mg/kg Rabbit	>6 mg/L Rat
1,2,4-trimethylbenzene	3280 mg/kg Rat	>3160 mg/kg Rabbit	18 mg/L Rat
crystalline silica	>5000 mg/kg	>5000 mg/kg	>20 mg/l Rat
methyl ethyl ketoxime	930 mg/kg Rat	1000 mg/kg Rabbit	>4.83 mg/L Rat
carbon black	>5000 mg/kg Rat	>3000 mg/kg Rabbit	>20 mg/l
cumene	1400 mg/kg Rat	10603 mg/kg Rabbit	>20 mg/l
	petroleum distillate m-xylene petroleum distillate o-xylene ethylbenzene n-butyl acetate p-xylene aromatic hydrocarbons propylene glycol monomethyl ether 1,2,4-trimethylbenzene crystalline silica methyl ethyl ketoxime carbon black	petroleum distillate >5000 mg/kg Rat m-xylene 5000 mg/kg Rat petroleum distillate >5000 mg/kg Rat o-xylene 3608 mg/kg Rat ethylbenzene 3500 mg/kg Rat n-butyl acetate 14130 mg/kg Rat p-xylene 4029 mg/kg Rat aromatic hydrocarbons 14000 mg/kg Rat propylene glycol monomethyl ether 5000 mg/kg Rat 1,2,4-trimethylbenzene 3280 mg/kg Rat crystalline silica >5000 mg/kg Rat methyl ethyl ketoxime 930 mg/kg Rat carbon black >5000 mg/kg Rat	petroleum distillate >5000 mg/kg Rat >3160 mg/kg Rabbit m-xylene 5000 mg/kg Rat 6500 mg/kg Rabbit petroleum distillate >5000 mg/kg Rat 3160 mg/kg Rabbit o-xylene 3608 mg/kg Rat 14100 mg/kg Rabbit ethylbenzene 3500 mg/kg Rat 15400 mg/kg Rabbit n-butyl acetate 14130 mg/kg Rat 15400 mg/kg Rabbit p-xylene 4029 mg/kg Rat >2000 mg/kg Rabbit aromatic hydrocarbons 14000 mg/kg Rat >2000 mg/kg Rabbit propylene glycol monomethyl ether 5000 mg/kg Rat 3160 mg/kg Rabbit 1,2,4-trimethylbenzene 3280 mg/kg Rat >3160 mg/kg Rabbit crystalline silica >5000 mg/kg Rat 1000 mg/kg Rabbit 1000 mg/kg Rabbit 25000 mg/kg R

## N.I. = No Information

# 12. Ecological information

**ECOLOGICAL INFORMATION:** Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

## 13. Disposal Information



## **Product**

**DISPOSAL METHOD:** Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the

special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

# 14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT: LIMITED QUANTITY

IATA: ID8000, CONSUMER COMMODITY, 9

IMDG: **LIMITED QUANTITY UN1263** 

## 15. Regulatory Information

## U.S. Federal Regulations:

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### **SARA SECTION 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>
m-xylene	108-38-3	7.34
o-xylene	95-47-6	3.33
ethylbenzene	100-41-4	2.96
p-xylene	106-42-3	2.88
1,2,4-trimethylbenzene	95-63-6	1.52
cumene	98-82-8	0.19

## TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical Name	<u>CAS-No.</u>
zinc	7440-66-6
lead	7439-92-1
mercury	7439-97-6

## **U.S. State Regulations:**

#### **CALIFORNIA PROPOSITION 65**



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Ethylbenzene, Cancer, 2.9576% Toluene, Reproductive Harm, 0.0174%

#### NOTICE

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in

# 16. Other Information

**Revision Date:** 7/27/2024 **Supersedes Date:** 6/14/2023

Reason for revision: Product Composition Changed

Substance and/or Product Properties Changed in Section(s):

01 - Product Information

03 - Composition/Information on Ingredients 08 - Exposure Controls/Personal Protection 09 - Physical & Chemical Information

15 - Regulatory Information16 - Other Information

Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 


Health:	2	Flammability:	3	Reactivity:	0	Personal Protection:	X

## Volatile Organic Compounds, gr/ltr: 411

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapor.
H251	Self-heating: may catch fire.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.

#### Icons for GHS Pictograms shown in Section 3 describing each ingredient:



#### **GHS08**



The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

Only the original U.S. - English version is authoritative.