

OUTDOOR ACRYLIC AEROSOL FLAT

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

M102-0910

OUTDOOR ACRYLIC AEROSOL FLAT

PRODUCT DESCRIPTION:

N/A

PHYSICAL PROPERTIES AND SPECIFICATIONS

Color clear Sheen 10 Viscosity N/A WPG 6.331314785 lbs/gal Solids by Volume 3.619368322 ±1% Solids by Weight 5.400330059 ±1% Flash Point -76.00000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 655.859866433 g/l Coating VOC (g/l) 416.420101139 g/l Material VOC (g/l) 416.420101139 g/l Material VOC (g/l) 416.420101139 g/l Material VOC (Lb/Gal) 3.475206559 lbs/gal #VOC/#Solid 10.164041117 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.434227716 Spread Rate 58.054667885 sq. ft/gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A Oven Dry N/A Shelf-Life (Unopened) 12 mo	Technology	ACRYLIC LACQUER
Viscosity N/A WPG 6.331314785 lbs/gal Solids by Volume 3.619368322 ±1% Solids by Weight 5.400330059 ±1% Flash Point -76.00000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 655.859866433 g/l Coating VOC (g/l) 655.859866433 g/l Coating VOC (g/l) 655.859866433 g/l Material VOC (g/l) 5.473435368 lbs/gal Material VOC (g/l) 416.420101139 g/l Material VOC (Lb/Gal) 3.475206559 lbs/gal #VOC/#Solid 10.164041117 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.434227716 Spread Rate 58.054667885 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Color	clear
WPG 6.331314785 lbs/gal Solids by Volume 3.619368322 ±1% Solids by Weight 5.400330059 ±1% Flash Point -76.00000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 655.859866433 g/l Coating VOC (g/l) 54.73435368 lbs/gal Material VOC (g/l) 416.420101139 g/l Material VOC (Lb/Gal) 3.475206559 lbs/gal #VOC/#Solid 10.164041117 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.434227716 Spread Rate 58.054667885 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Sheen	10
Solids by Volume 3.619368322 ±1% Solids by Weight 5.400330059 ±1% Flash Point -76.0000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 655.859866433 g/l Coating VOC (g/l) 655.859866433 g/l Coating VOC (g/l) 5.473435368 lbs/gal Material VOC (g/l) 416.420101139 g/l Material VOC (b/Gal) 3.475206559 lbs/gal #VOC/#Solid 10.164041117 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.434227716 Spread Rate 58.054667885 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Viscosity	N/A
Solids by Weight 5.400330059 ±1% Flash Point -76.00000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 655.859866433 g/l Coating VOC (Lb/Gal) 5.473435368 lbs/gal Material VOC (g/l) 416.420101139 g/l Material VOC (Lb/Gal) 3.475206559 lbs/gal #VOC/#Solid 10.164041117 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.434227716 Spread Rate 58.054667885 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A	WPG	6.331314785 lbs/gal
Flash Point -76.00000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 655.859866433 g/l Coating VOC (Lb/Gal) 5.473435368 lbs/gal Material VOC (g/l) 416.420101139 g/l Material VOC (Lb/Gal) 3.475206559 lbs/gal #VOC/#Solid 10.164041117 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.434227716 Spread Rate 58.054667885 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Solids by Volume	3.619368322 ±1%
HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 655.859866433 g/l Coating VOC (Lb/Gal) 5.473435368 lbs/gal Material VOC (g/l) 416.420101139 g/l Material VOC (Lb/Gal) 3.475206559 lbs/gal #VOC/#Solid 10.164041117 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.434227716 Spread Rate 58.054667885 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Solids by Weight	5.400330059 ±1%
Coating VOC (g/l) 655.859866433 g/l Coating VOC (Lb/Gal) 5.473435368 lbs/gal Material VOC (g/l) 416.420101139 g/l Material VOC (Lb/Gal) 3.475206559 lbs/gal #VOC/#Solid 10.164041117 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.434227716 Spread Rate 58.054667885 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Flash Point	-76.00000000 °F
Coating VOC (Lb/Gal)5.473435368 lbs/galMaterial VOC (g/l)416.420101139 g/lMaterial VOC (Lb/Gal)3.475206559 lbs/gal#VOC/#Solid10.164041117 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.434227716Spread Rate58.054667885 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)12 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	HMIS	H: 2, F: 4, R: 0, P: X
Material VOC (g/l)416.420101139 g/lMaterial VOC (Lb/Gal)3.475206559 lbs/gal#VOC/#Solid10.164041117 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.434227716Spread Rate58.054667885 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)12 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Coating VOC (g/l)	655.859866433 g/l
Material VOC (Lb/Gal)3.475206559 lbs/gal#VOC/#Solid10.164041117 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.434227716Spread Rate58.054667885 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)12 monthsPot-Life (Catalyzed)N/AN/A	Coating VOC (Lb/Gal)	5.473435368 lbs/gal
#VOC/#Solid10.164041117 lbs/lbs solidVHAP Ratio (#VHAP/#Solid)0.434227716Spread Rate58.054667885 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)12 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Material VOC (g/l)	416.420101139 g/l
VHAP Ratio (#VHAP/#Solid)0.434227716Spread Rate58.054667885 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)12 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Material VOC (Lb/Gal)	3.475206559 lbs/gal
Spread Rate58.054667885 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)12 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	#VOC/#Solid	10.164041117 lbs/lbs solid
Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)12 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	VHAP Ratio (#VHAP/#Solid)	0.434227716
ReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)12 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Spread Rate	58.054667885 sq. ft./gal @ 1.0 mil DFT (no loss)
RetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)12 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Catalyst/Ratio	N/A
AirDryN/AOven DryN/AShelf-Life (Unopened)12 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Reducer	N/A
Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Retarder	N/A
Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	AirDry	N/A
Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Oven Dry	N/A
Recoat Instruction N/A	Shelf-Life (Unopened)	12 months
	Pot-Life (Catalyzed)	N/A
	Recoat Instruction	N/A
	PH	N/A

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.