

QUIK-TIP MARKER MATTE CREAM UC

PRODUCT NUMBER

DESCRIPTION

M290-2287

QUIK-TIP MARKER MATTE CREAM UC

PRODUCT DESCRIPTION:

TECHNICAL DATA SHEET

N/A

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology N/A Color N/A Sheen N/A Viscosity N/A WPG 9.711186839 lbs/gal Solids by Volume 33.766944804 ±1% Solids by Weight 49.937342780 ±1% Flash Point 39.200000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 582.518281587 g/l Coating VOC (Lb/Gal) 4.861367997 lbs/gal Material VOC (g/l) 582.469582285 g/l Material VOC (Lb/Gal) 4.860961580 lbs/gal #VOC/#Solid 1.002361666 lbs/lbs solid VHAP Ratic (#VHAP/#Solid) 0.861390399 Spread Rate 541.621794656 sq. ft./gal @ 1.0 mill DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A Ph N/A		
Sheen N/A Viscosity N/A WPG 9.711186839 lbs/gal Solids by Volume 33.766944804 ±1% Solids by Weight 49.937342780 ±1% Flash Point 39.20000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 582.518281587 g/l Coating VOC (Lb/Gal) 4.861367997 lbs/gal Material VOC (g/l) 582.469582285 g/l Material VOC (tb/Gal) 4.860961580 lbs/gal #VOC/#Solid 1.002361666 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.861390399 Spread Rate 541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Technology	N/A
Viscosity N/A WPG 9.711186839 lbs/gal Solids by Volume 33.766944804 ±1% Solids by Weight 49.937342780 ±1% Flash Point 39.20000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 582.518281587 g/l Coating VOC (Lb/Gal) 4.861367997 lbs/gal Material VOC (g/l) 582.469582285 g/l Material VOC (Lb/Gal) 4.860961580 lbs/gal #VOC/#Solid 1.002361666 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.861390399 Spread Rate 541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Color	N/A
WPG 9.711186839 lbs/gal Solids by Volume 33.766944804 ±1% Solids by Weight 49.937342780 ±1% Flash Point 39.200000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 582.518281587 g/l Coating VOC (Lb/Gal) 4.861367997 lbs/gal Material VOC (g/l) 582.469582285 g/l Material VOC (Lb/Gal) 4.860961580 lbs/gal #VOC/#Solid 1.002361666 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.861390399 Spread Rate 541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Sheen	N/A
Solids by Volume 33.766944804 ±1% Solids by Weight 49.937342780 ±1% Flash Point 39.200000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 582.518281587 g/l Coating VOC (Lb/Gal) 4.861367997 lbs/gal Material VOC (g/l) 582.469582285 g/l Material VOC (Lb/Gal) 4.860961580 lbs/gal #VOC/#Solid 1.002361666 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.861390399 Spread Rate 541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Viscosity	N/A
Solids by Weight 49.937342780 ± 1% Flash Point 39.200000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 582.518281587 g/l Coating VOC (Lb/Gal) 4.861367997 lbs/gal Material VOC (g/l) 582.469582285 g/l Material VOC (Lb/Gal) 4.860961580 lbs/gal #VOC/#Solid 1.002361666 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.861390399 Spread Rate 541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	WPG	9.711186839 lbs/gal
Flash Point 39.20000000 °F HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/l) 582.518281587 g/l Coating VOC (Lb/Gal) 4.861367997 lbs/gal Material VOC (g/l) 582.469582285 g/l Material VOC (Lb/Gal) 4.860961580 lbs/gal #VOC/#Solid 1.002361666 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.861390399 Spread Rate 541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Solids by Volume	33.766944804 ±1%
HMIS H: 2, F: 3, R: 0, P: X Coating VOC (g/I) 582.518281587 g/I Coating VOC (Lb/Gal) 4.861367997 lbs/gal Material VOC (g/I) 582.469582285 g/I Material VOC (Lb/Gal) 4.860961580 lbs/gal #VOC/#Solid 1.002361666 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.861390399 Spread Rate 541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Solids by Weight	49.937342780 ±1%
Coating VOC (g/l) 582.518281587 g/l Coating VOC (Lb/Gal) 4.861367997 lbs/gal Material VOC (g/l) 582.469582285 g/l Material VOC (Lb/Gal) 4.860961580 lbs/gal #VOC/#Solid 1.002361666 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.861390399 Spread Rate 541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Flash Point	39.200000000 °F
Coating VOC (Lb/Gal) 4.861367997 lbs/gal Material VOC (g/l) 582.469582285 g/l Material VOC (Lb/Gal) 4.860961580 lbs/gal #VOC/#Solid 1.002361666 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.861390399 Spread Rate 541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	HMIS	H: 2, F: 3, R: 0, P: X
Material VOC (g/l) 582.469582285 g/l Material VOC (Lb/Gal) 4.860961580 lbs/gal #VOC/#Solid 1.002361666 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.861390399 Spread Rate 541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Coating VOC (g/I)	582.518281587 g/l
Material VOC (Lb/Gal) 4.860961580 lbs/gal #VOC/#Solid 1.002361666 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.861390399 Spread Rate 541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Coating VOC (Lb/Gal)	4.861367997 lbs/gal
#VOC/#Solid 1.002361666 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.861390399 Spread Rate 541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Material VOC (g/l)	582.469582285 g/l
VHAP Ratio (#VHAP/#Solid) 0.861390399 Spread Rate 541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Material VOC (Lb/Gal)	4.860961580 lbs/gal
Spread Rate541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	#VOC/#Solid	1.002361666 lbs/lbs solid
Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	VHAP Ratio (#VHAP/#Solid)	0.861390399
Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Spread Rate	541.621794656 sq. ft./gal @ 1.0 mil DFT (no loss)
Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Catalyst/Ratio	N/A
AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Reducer	N/A
Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Retarder	N/A
Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	AirDry	N/A
Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Oven Dry	N/A
Recoat Instruction N/A	Shelf-Life (Unopened)	36 months
	Pot-Life (Catalyzed)	N/A
PH N/A	Recoat Instruction	N/A
	PH	N/A

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.