



POLY-BUF RUBBING COMPOUND EXTRA FINE LEVEL III QT

TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
M890-0036	POLY-BUF RUBBING COMPOUND EXTRA FINE LEVEL III QT

PRODUCT DESCRIPTION:

POLY-BUF™ RUBBING COMPOUND - Level III (Super High Sheen) Compounds used after Step 3 Finishing Compounds to achieve the high gloss "wet look." Start with the medium grade for initially rubbing out a refinished surface. Use the fine grade for rubbing fine scratches and the extra fine grade for extra fine scratches and increasing the gloss. Available in 8 oz or gallon.

ADVANTAGES:

1. Semi Paste form.
2. Quick clean-up.
3. Best performance with machine buffing.

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	N/A
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	8.395241020 lbs/gal
Solids by Volume	9.780984867 ±1%
Solids by Weight	10.900000000 ±1%
Flash Point	200.000000000 °F
HMIS	H: 1, F: 1, R: 0, P: X
Coating VOC (g/l)	429.434660498 g/l
Coating VOC (Lb/Gal)	3.583818708 lbs/gal
Material VOC (g/l)	91.543101714 g/l
Material VOC (Lb/Gal)	0.763966933 lbs/gal
#VOC/#Solid	0.834862385 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.004495413
Spread Rate	156.886997267 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	24 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

Water - CAS 7732-18-5 - solvent
Glycerin - CAS 56-81-5 - luster/shine
C9-12 Light Alkanes - CAS 64742-88-7 - solvent
Mineral Oil - CAS 8042-47-5 - lubricant
Titanium Dioxide - CAS 13463-67-7 - abrasive

DIRECTIONS:

Poly-Buf may be applied by hand or low speed buffer. Shake well before using. Apply to surface and buff in a circular motion using a clean dry cloth or buffing pad. Allow to haze. Buff to a high gloss with a clean soft cloth. Follow Poly-Buf™ Rubbing Compound Extra Fine with a high gloss polish such as Mohawk OZ® Polish to produce a mirror-like finish.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.