



UPHOLSTERY, FABRIC CLEANER

TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
M103-3001, M898-86143	UPHOLSTERY, FABRIC CLEANER

PRODUCT DESCRIPTION:

No Bleach. Cleans grease, ink, crayon, red drinks, lipstick, cosmetics, iodine, blood, sun block, shoe polish and much more. This product can be used to remove stains on washable textiles and carpeting. Protect from freezing.

ADVANTAGES:

1. New 32 oz trigger Spray
2. Low VOC
3. No Bleach

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	N/A
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	8.378684355 lbs/gal
Solids by Volume	1.384211682 ±1%
Solids by Weight	1.801007143 ±1%
Flash Point	200.000000000 °F
HMIS	H: 1, F: 0, R: 0, P: X
Coating VOC (g/l)	244.292436877 g/l
Coating VOC (Lb/Gal)	2.038726461 lbs/gal
Material VOC (g/l)	4.547190000 g/l
Material VOC (Lb/Gal)	0.037948275 lbs/gal
#VOC/#Solid	0.251478451 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	22.202755379 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	12 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	10.7

Water - CAS 7732-18-5 - solvent
C9-11 Alcohols Ethoxylated - CAS 68439-46-3 - surfactant
Sodium Carbonate Peroxide - CAS 15630-89-4 - oxidizer
Dipropylene Glycol Methyl Ether - CAS 34590-94-8 - solvent
Potassium Sorbate - CAS 24634-61-5 - preservative
Alcohols, C9-11 - CAS 66455-17-2 - surfactant
Polyalkylene Glycol - CAS 9003-11-6 - defoamer

DIRECTIONS:

Pre-test on an inconspicuous area before using. Carefully remove any excess spillage and apply Cleaner. Allow cleaner to remain on problem area for a few minutes. Lightly agitate spot with a soft bristled brush. Blot up cleaner with a clean absorbent towel or cloth. Rinse with water and blot (extract) again.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.